



QPZ Centrifugal Fan

For high pressure applications

QPZ Kit DATA SHEET

Centrifugal Fan (Customer Assembly Kit)

The QPZ Customer Assembly Kit was designed to reduce customer costs and storage space by delivering the range in an easy to assemble component form. This range can still be customised to suit including assemblies, nameplates, paint, colour and local motor etc.

KEY FEATURES

- Duties ranging from 0.02m³/5 - 1.7m³/5.
- Range of sizes allows for most industrial needs to be met.

TECHNICAL DATA

- Outlet (mm): 50, 65, 75, 100, 125, 150
- Impeller Range (mm): 300 to 900
- 2, 4, 6, 8 pole motors or inverter speed control
- Suitable for 50 / 60 Hz supplies: 1 phase / 3 phase
- Pressed Casing, Welded Pedestal and Riveted Impeller
- Double-Skin (insulated) construction available
- Mild Steel
- Taper-Lock or Positively Located Welded Hub

SPECIFICATIONS

- Available in Left and Right Hand Format
- Various Orientations
- Direct or Belt Drive
- Standard Paint or Range of Special Finishes
- Standard Motor is IP55
- Guarded Inlet As Standard
- Temperature range of -10oC to +40oC



Fans & Blowers Ltd
Commerce Way
Walrow Industrial Estate
Highbridge, Somerset, TA9 4AG

T: 01278 784 004
info@fansandblowers.com
fansandblowers.com

ANCILLARIES

- Filters
- Silencers
- Flexible Connections
- Spigots
- ANSI flanges
- Anti-Vibration Mounts

TESTING & STANDARDS

- Can be designed and manufactured to ATEX certified specifications.
- Designed and manufactured to ISO 9001:2008 standards.
- Tested to BS 848 / ISO 5801 standards

INDUSTRIES & APPLICATIONS

The QPZ range of centrifugal fans can often be seen to support air knives in industries such as **waste management**. This range also suits combustion air applications in **cremation, incineration, ovens** and kilns. For specific and bespoke applications, please contact us.